




## DIMENSIONS



# MODEL 4801A ACCELEROMETER

## SPECIFICATIONS

- ◆ Amplified, Signal Conditioned
- ◆ MEMS DC Response
- ◆ Hermetically Sealed, Detachable Cable
- ◆ -55°C to +125°C Operating Range

The Model 4801A is a true hermetically sealed accelerometer in a rugged stainless steel package. The offers an amplified signal conditioned output in ranges from  $\pm 2$  to  $\pm 200g$ . The model 4801A incorporates enhanced temperature compensation and a gas damped MEMS sensing element for optimum frequency response. Mechanical over-range stops offers shock protection up to 5,000g designed for both static and dynamic measurements in critical applications.

## FEATURES

- ◆  $\pm 2g$  to  $\pm 200g$  Dynamic Range
- ◆ Amplified Output
- ◆ 8-36Vdc Excitation Voltage
- ◆ Gas Damped MEMS Element
- ◆ Detachable Cable
- ◆ DC to 1500Hz Response
- ◆ Stud Mounting

## APPLICATIONS

- ◆ Vehicle Testing
- ◆ Structural Testing
- ◆ Test & Instrumentation
- ◆ Transportation Measurements
- ◆ Environmental Testing

## PERFORMANCE SPECIFICATIONS



All values are typical at +24°C, 80Hz and 12Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice.

Parameters								Notes
DYNAMIC								
Range (g)	±2	±5	±10	±20	±50	±100	±200	±5%
Sensitivity (mV/g)	1000	400	200	100	40	20	10	
Frequency Response (Hz)	0-250	0-700	0-1000	0-1000	0-1000	0-1000	0-1000	
Natural Frequency (Hz)	700	800	1000	1500	4000	6000	8000	
Non-Linearity (%FSO)	±1.0	±1.0	±1.0	±1.0	±1.0	±1.0	±1.0	
Transverse Sensitivity (%)	<3	<3	<3	<3	<3	<3	<3	<1 Typical
Damping Ratio	0.7	0.7	0.7	0.7	0.7	0.7	0.6	Passband
Shock Limit (g)	5000	5000	5000	5000	5000	5000	5000	
Residual Noise (µV RMS)	600	750	800	800	800	400	400	
Spectral Noise (µg/√Hz)	35	38	75	132	316	516	1033	Passband
ELECTRICAL								
Zero Acceleration Output (mV)	±50							Differential
Excitation Voltage (Vdc)	8 to 36							@100Vdc
Excitation Current (mA)	<5							
Bias Voltage (Vdc)	2.5							
Full Scale Output Voltage (V)	±2							
Output Resistance (Ω)	<100							
Insulation Resistance (MΩ)	>100							
Turn On Time (msec)	<100							
Ground Isolation	Isolated from Mounting Surface							
ENVIRONMENTAL								
Thermal Zero Shift (%FSO/°C)	±0.004							Typical
Thermal Sensitivity Shift (%/°C)	±0.010							
Operating Temperature (°C)	-55 to 125							Typical
Storage Temperature (°C)	-55 to 125							
Humidity	Hermetically Sealed, IP67 <sup>1</sup>							
PHYSICAL								
Case Material	Stainless Steel							
Weight (grams)	22							
Mounting	#10-32 to #10-32 Mounting Stud (included)							
Mounting Torque	18 lb-in (2.0 N-m)							

<sup>1</sup> Mating cable needs to also have minimum IP67 rating and be properly sealed to accel connector in accordance with IEC 60529.

<b>Calibration supplied:</b>	CS-FREQ-0100	NIST Traceable Amplitude Calibration from 20Hz to ±5% Frequency Response Limit <sup>1</sup>
<b>Supplied accessories:</b>	AC-D02298	10-32 to 10-32 mounting stud
<b>Optional accessories:</b>	340A-XXX	Cable Assembly, #28 AWG, -54 to +121°C (XXX designates length in inches, 5ft standard)
	343-XXX	Cable Assembly, #28 AWG, -40 to +85°C (XXX designates length in inches, 5ft standard)
	121	3-Channel Precision Low Noise DC Amplifier
	AC-D02741	Adhesive Mounting Adaptor
	AC-D04716	Triaxial Mounting Block

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.



### ORDERING INFORMATION

PART NUMBERING    Model Number+Range

4801A-GGGG-C

I  
I \_\_\_\_\_ Range (0010 is 10g)

Example: 4801A-0010-C

Model 4801A, 10g

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.